




DIMENSIONS



ACCESSORIES



LARK

Name	ORBITAL MINI 1 LARK N
Reference	A1961100N
Color	Matt black
RAL	9005
Category	CEILING RECESSED

PRODUCT

Type	LARK EXCL
Power	Max 1 X 7,5 W
LED lifespan	L80B10 >60.000h

LIGHT SOURCE

Driver	Excluded
Dimming	No Dim / DALI / Push / Phase Cut
Electrical insulation class	<input type="checkbox"/>

LIGHTING FIXTURE | ELECTRICAL DATA



Sealing	IP20
Wireless control	Please Consult
Emergency power supply	Please Consult
Recess measurements	113 x 113 mm
Swivel angle	X30° Y30°
Weight	650 g
Packaged weight	795 g
Packaging dimensions	167 x 154 x 154 mm
Units per package	1
Materials	Aluminium

OTHER DATA




Orbital Mini is a ceiling recessed luminaire whose beam can be directed in an angle of up to 30 degrees per axis. Versatile, functional and -due to its small size- very discrete and elegant.



		P	CCT	I	Flux	Flux Out	LOR
LARK	0434-00-96	5W	2700K	140mA	700Lm	644Lm	92%
	0434-00-05	5W	3000K	140mA	730Lm	672Lm	92%
	0434-00-19	5W	4000K	140mA	750Lm	690Lm	92%
	0434-01-02	7,5W	2700K	200mA	950Lm	874Lm	92%
	0434-00-09	7,5W	3000K	200mA	1000Lm	920Lm	92%
	0434-00-17	7,5W	4000K	200mA	1030Lm	948Lm	92%
	0434-01-03	7,5W	2700K	200mA	950Lm	874Lm	92%
	0434-00-15	7,5W	3000K	200mA	1000Lm	920Lm	92%
 PHASE CUT *	0434-00-18	7,5W	4000K	200mA	1030Lm	948Lm	92%
	0434-01-04	7,5W	2700K	200mA	950Lm	874Lm	92%
 DALI PUSH *	0434-01-05	7,5W	3000K	200mA	1000Lm	920Lm	92%
	0434-01-06	7,5W	4000K	200mA	1030Lm	948Lm	92%

LED | 220-240 V~ | CE | CRI>80 | > 60.000h L80B10

 MacAdam Step 2 |
  INCL |
  FAST | CONNEC |
  38°



* OTHER DIM OPTIONS PLEASE CONSULT

 &  » PLEASE CONSULT



Fuente de luz (LED) reemplazable por un profesional autorizado
 Replaceable (LED only) light source by an authorized professional.
 Source lumineuse (LED) remplaçable par un professionnel agréé
 Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato
 Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado
 Replaceable control gear by an authorized professional
 Dispositif de commande remplaçable par un professionnel agréé
 Alimentatore sostituibile da parte di un professionista autorizzato
 Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES
 INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL
 INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT
 ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI
 ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN



Interrumpir la alimentación del aparato
 Cut the power supply to the luminaire
 Couper l'alimentation du luminaire
 Interrompere l'alimentazione dell'apparecchio
 Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho
 Remove light source(s) for disposal
 Retirer la (les) source(s) lumineuse(s) pour l'élimination
 Rimuovere la/le sorgente/e di luce per lo smaltimento
 Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho
 Remove the battery for decommissioning
 Retirer la batterie pour sa mise au rebut
 Rimuovere la batteria per la dismissione
 Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho
 Remove control gear for disposal
 Retirer le dispositif de commande pour l'élimination
 Rimuovere l'alimentatore per lo smaltimento
 Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE
 Send the materials to a WEEE collection centre
 Envoyer les matériaux dans une déchetterie DEEE
 Inviare i materiali ad un centro di raccolta RAEE
 Die Materialien in einem WEEE-Zentrum entsorgen

