




DIMENSIONS



AWARDS



Name	PUCK L 3000K NT
Reference	A2512001NT
Color	Textured black
RAL	9005
Category	SURFACE

PRODUCT

Type	LED
Gross luminous flux	1280 lm
Colour temperature	3000 K
Chromatic stability	MacAdam Step 3
Colour Rendering Index	CRI > 90
Power	15 W
Efficacy	85 lm/W
LED lifespan	L70B10 > 50.000h

LIGHT SOURCE

Lighting efficiency	80%
Light beam angle	37°

LIGHTING FIXTURE | PHOTOMETRIC DATA

Driver	Included
Power values of the system	20,00 W
Frequency	50/60 Hz
Dimming	No Dim
Electrical insulation class	⚡

LIGHTING FIXTURE | ELECTRICAL DATA


Sealing	IP20
Weight	510 g
Packaged weight	570 g
Packaging dimensions	134 x 119 x 73,5 mm
Units per package	1
Materials	Aluminium / Optical Glass

OTHER DATA




Puck is a luminary that –for its function, opening angle and luminous flux- manages to embody, in a surface piece, the performance of the classic recessed luminaries with dichroic lamps. Puck is designed to undertake general lighting functions and, moreover, given its ultra-compact format, aims to conserve discretion in those places where it is impossible to recess the appliances in the ceiling.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR																							
p Ceiling		70	70	50	50	30	30	70	70	50	50	30	30										
p Walls		50	30	50	30	30	30	50	30	50	30	30	30										
p Floor		20	20	20	20	20	20	20	20	20	20	20	20										
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis																
2H	2H	6.4	7.1	6.7	7.3	7.5	6.5	7.2	6.7	7.4	7.6	4H	2H	6.8	7.4	7.1	7.7	7.9	6.9	7.5	7.2	7.7	8.0
	3H	8.7	9.3	9.0	9.6	9.8	8.8	9.5	9.1	9.7	9.9		3H	9.7	10.2	10.0	10.5	10.8	9.8	10.3	10.1	10.6	10.9
	4H	9.8	10.4	10.1	10.6	10.9	9.9	10.5	10.2	10.7	11.0		4H	10.9	11.3	11.2	11.6	12.0	11.0	11.4	11.3	11.7	12.1
	6H	10.3	10.8	10.6	11.1	11.4	10.5	11.0	10.8	11.3	11.5		6H	11.5	11.8	11.9	12.2	12.6	11.6	12.0	12.0	12.3	12.7
	8H	10.5	11.0	10.8	11.3	11.6	10.6	11.2	11.0	11.4	11.7		8H	11.7	12.0	12.1	12.4	12.8	11.9	12.2	12.3	12.6	13.0
4H	12H	10.6	11.1	11.0	11.4	11.7	10.8	11.3	11.1	11.6	11.9	12H	11.9	12.2	12.3	12.6	13.0	12.0	12.3	12.5	12.7	13.1	
	2H	6.8	7.4	7.1	7.7	7.9	6.9	7.5	7.2	7.7	8.0	8H	4H	11.3	11.6	11.7	12.0	12.4	11.4	11.7	11.8	12.0	12.4
	3H	9.7	10.2	10.0	10.5	10.8	9.8	10.3	10.1	10.6	10.9		6H	12.0	12.2	12.5	12.7	13.1	12.1	12.3	12.6	12.8	13.2
	4H	10.9	11.3	11.2	11.6	12.0	11.0	11.4	11.3	11.7	12.1		8H	12.3	12.5	12.8	12.9	13.4	12.4	12.6	12.9	13.1	13.5
	6H	11.5	11.8	11.9	12.2	12.6	11.6	12.0	12.0	12.3	12.7		12H	12.6	12.7	13.0	13.2	13.7	12.7	12.8	13.2	13.3	13.8
8H	11.7	12.0	12.1	12.4	12.8	11.9	12.2	12.3	12.6	13.0	12H		4H	11.3	11.6	11.7	12.0	12.4	11.4	11.6	11.8	12.0	12.5
12H	11.9	12.2	12.3	12.6	13.0	12.0	12.3	12.5	12.7	13.1		6H	12.1	12.3	12.5	12.7	13.2	12.2	12.4	12.6	12.8	13.3	
2H	6.4	7.1	6.7	7.3	7.5	6.5	7.2	6.7	7.4	7.6		8H	12.4	12.6	12.9	13.0	13.5	12.5	12.7	13.0	13.2	13.6	
3H	8.7	9.3	9.0	9.6	9.8	8.8	9.5	9.1	9.7	9.9		Variation of the observer position for the luminaire distances S											
4H	9.8	10.4	10.1	10.6	10.9	9.9	10.5	10.2	10.7	11.0		S = 1.0H	+3.9	-2.6	+3.8	-2.5							
6H	10.3	10.8	10.6	11.1	11.4	10.5	11.0	10.8	11.3	11.5	S = 1.5H	+6.3	-3.1	+6.3	-3.1								
8H	10.5	11.0	10.8	11.3	11.6	10.6	11.2	11.0	11.4	11.7	S = 2.0H	+8.3	-3.4	+8.2	-3.4								
12H	10.6	11.1	11.0	11.4	11.7	10.8	11.3	11.1	11.6	11.9	Standard table	BK02		BK02									
2H	6.8	7.4	7.1	7.7	7.9	6.9	7.5	7.2	7.7	8.0	Correction												
3H	9.7	10.2	10.0	10.5	10.8	9.8	10.3	10.1	10.6	10.9	Summand	-4.6		-4.5									
4H	10.9	11.3	11.2	11.6	12.0	11.0	11.4	11.3	11.7	12.1	Corrected Glare Indices referring to 1280lm Total Luminous Flux												
6H	11.5	11.8	11.9	12.2	12.6	11.6	12.0	12.0	12.3	12.7													
8H	11.7	12.0	12.1	12.4	12.8	11.9	12.2	12.3	12.6	13.0													
12H	11.9	12.2	12.3	12.6	13.0	12.0	12.3	12.5	12.7	13.1													



Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES
 INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL
 INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT
 ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI
 ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN



Interrumpir la alimentación del aparato
 Cut the power supply to the luminaire
 Couper l'alimentation du luminaire
 Interrompere l'alimentazione dell'apparecchio
 Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho
 Remove light source(s) for disposal
 Retirer la (les) source(s) lumineuse(s) pour l'élimination
 Rimuovere la/le sorgente/e di luce per lo smaltimento
 Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho
 Remove the battery for decommissioning
 Retirer la batterie pour sa mise au rebut
 Rimuovere la batteria per la dismissione
 Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho
 Remove control gear for disposal
 Retirer le dispositif de commande pour l'élimination
 Rimuovere l'alimentatore per lo smaltimento
 Betriebsgerät zur Entsorgung ausbauen



Enviar los materiales a un centro de recogida RAEE
 Send the materials to a WEEE collection centre
 Envoyer les matériaux dans une déchetterie DEEE
 Inviare i materiali ad un centro di raccolta RAEE
 Die Materialien in einem WEEE-Zentrum entsorgen

