



DIMENSIONS



AWARDS



Name	BLACK FOSTER REC 2X2 SPOT DIM PH.CUT 3500K WN
Reference	A3195153WN
Color	White-Black
RAL	Colour in the mass looks alike RAL 9016 & 9005
Category	CEILING RECESSED

Type	LED
Gross luminous flux	920 lm
Colour temperature	3500 K
Chromatic stability	MacAdam Step 3
Colour Rendering Index	CRI>90
Power	8,4 W
Current	700 mA
Efficacy	110 lm/W
LED lifespan	L90B10 >102.000h

Lighting efficiency	90%
Light beam angle	19°

Driver	Included - Connected
Power values of the system	11,78 W
Frequency	50/60 Hz
Dimming	Phase Cut
Electrical insulation class	□

Sealing	IP20
Wireless control	Please Consult
Emergency power supply	Please Consult
Recess measurements	93 x 93 mm
Weight	221 g
Packaged weight	321 g
Packaging dimensions	178 x 135 x 50 mm
Units per package	1
Materials	Aluminium / Acrylonitrile Butadiene Styrene

PRODUCT

LIGHT SOURCE

LIGHTING FIXTURE | PHOTOMETRIC DATA

LIGHTING FIXTURE | ELECTRICAL DATA


OTHER DATA




Black Foster is the product that transfers the claimed effect "The Invisible Black" to a recessed-isolated lineal luminary; also available in trimless version. If we take a closer view to the recessed model, its bezel is so thin than when lighted up, it is unperceived; offering an aesthetic of "visual trimless". Black Foster stands out for its refinement, its visual comfort and for almost completely hide the source of light from the human eye range.



POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Valoración de deslumbramiento según UGR													
ρ Techo	70	70	50	50	30	70	50	50	30	30			
ρ Paredes	50	30	50	30	30	50	30	50	30	30			
ρ Suelo	20	20	20	20	20	20	20	20	20	20			
Tamaño del local	Mirado en perpendicular al eje de lámpara					Mirado longitudinalmente al eje de lámpara							
X	Y	2H	3H	4H	6H	8H	12H	2H	3H	4H	6H	8H	12H
2H	2H	2.8	3.5	3.0	3.6	3.8	3.3	3.9	3.5	4.1	4.3	7.8	7.8
	3H	6.0	6.6	6.3	6.8	7.1	6.7	7.3	7.0	7.6	7.8	9.8	9.8
	4H	7.8	8.4	8.1	8.6	8.9	8.7	9.3	9.0	9.5	9.8	12.0	12.0
	6H	9.9	10.4	10.2	10.7	11.0	10.9	11.5	11.2	11.7	12.0	13.3	13.3
	8H	11.0	11.5	11.3	11.8	12.1	12.2	12.7	12.5	13.0	13.3	14.7	14.7
	12H	12.4	12.8	12.7	13.1	13.5	13.6	14.1	13.9	14.4	14.7	16.5	16.5
4H	2H	4.0	4.6	4.3	4.9	5.1	4.4	4.9	4.7	5.2	5.5	9.2	9.2
	3H	7.4	7.9	7.8	8.2	8.5	8.1	8.5	8.4	8.8	9.2	11.2	11.2
	4H	9.4	9.9	9.8	10.2	10.5	10.2	10.6	10.5	10.9	11.2	13.6	13.6
	6H	11.6	12.0	12.0	12.3	12.7	12.5	12.9	12.9	13.2	13.6	14.9	14.9
	8H	12.8	13.1	13.2	13.5	13.9	13.9	14.2	14.3	14.5	14.9	17.9	17.9
	12H	14.3	14.5	14.7	14.9	15.4	15.4	15.7	15.8	16.1	16.5	19.9	19.9
8H	4H	10.4	10.7	10.8	11.1	11.5	10.9	11.2	11.3	11.6	12.0	14.6	14.6
	6H	12.7	13.0	13.2	13.4	13.8	13.5	13.7	13.9	14.1	14.6	16.1	16.1
	8H	14.1	14.3	14.6	14.8	15.2	15.0	15.2	15.5	15.6	16.1	17.9	17.9
	12H	15.8	15.9	16.2	16.4	16.9	16.7	16.9	17.2	17.4	17.9	20.9	20.9
12H	4H	10.6	10.9	11.0	11.3	11.7	11.1	11.4	11.5	11.8	12.2	14.9	14.9
	6H	13.1	13.3	13.6	13.7	14.2	13.8	14.0	14.2	14.4	14.9	16.0	16.0
	8H	14.6	14.8	15.1	15.2	15.7	15.4	15.5	15.9	16.0	16.5	18.0	18.0
Variación de la posición del espectador para separaciones S entre luminarias													
S = 1.0H	+0.2 / -0.1					+0.2 / -0.1							
S = 1.5H	+0.3 / -0.3					+0.3 / -0.3							
S = 2.0H	+0.5 / -0.5					+0.5 / -0.5							
Tabla estándar Sumando de corrección	---					---							
Índice de deslumbramiento corregido en relación a 920lm Flujo luminoso total													



## DRIVER

0000-96-39	DRIVER 10W 700mA PHASE CUT
------------	----------------------------

## PHASE CUT DIMMERS TESTED FOR COMPATIBILITY:

Brand / Manufacturer	Model number	Dimming Type
Niko	310-0190X	Trailing edge
Jung	LB-Management	Trailing edge
HZC Electric	AU-P3	Trailing edge
Philips	SED-200A	Trailing edge
Merten/Schneider	SBD315RC	Trailing edge
Etman	ETM327	Trailing edge
Etman	ETM329	Trailing edge
Casambi	CBU-TED	Trailing edge

THE PARTICULAR CONDITIONS OF EACH INSTALLATION AND THE SPECIFICATIONS AND CONDITIONS OF USE OF EACH REGULATOR, MAY DIFFER FROM THOSE CONSIDERED IN THE COMPATIBILITY TESTING, AND AFFECT ITS PERFORMANCE IN SAID INSTALLATION.

FOR MORE INFO, PLEASE CONSULT



Fuente de luz (LED) reemplazable por un profesional autorizado  
 Replaceable (LED only) light source by an authorized professional.  
 Source lumineuse (LED) remplaçable par un professionnel agréé  
 Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato  
 Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado  
 Replaceable control gear by an authorized professional  
 Dispositif de commande remplaçable par un professionnel agréé  
 Alimentatore sostituibile da parte di un professionista autorizzato  
 Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES  
 INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL  
 INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT  
 ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI  
 ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN



Interrumpir la alimentación del aparato  
 Cut the power supply to the luminaire  
 Couper l'alimentation du luminaire  
 Interrompere l'alimentazione dell'apparecchio  
 Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho  
 Remove light source(s) for disposal  
 Retirer la (les) source(s) lumineuse(s) pour l'élimination  
 Rimuovere la/le sorgente/e di luce per lo smaltimento  
 Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho  
 Remove the battery for decommissioning  
 Retirer la batterie pour sa mise au rebut  
 Rimuovere la batteria per la dismissione  
 Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho  
 Remove control gear for disposal  
 Retirer le dispositif de commande pour l'élimination  
 Rimuovere l'alimentatore per lo smaltimento  
 Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE  
 Send the materials to a WEEE collection centre  
 Envoyer les matériaux dans une déchetterie DEEE  
 Inviare i materiali ad un centro di raccolta RAEE  
 Die Materialien in einem WEEE-Zentrum entsorgen

