




## Dimensions



## Accessories



ADD-ON BEZEL EXCLUDED.  
NOT COMPATIBLE.

## Awards



|           |                           |
|-----------|---------------------------|
| Name      | SWAP M RT 2012 7W 3500K Z |
| Reference | A4122213Z                 |
| Colour    | Aluminium                 |
| RAL       | 9006                      |
| Category  | CEILING RECESSED          |

|                         |                 |
|-------------------------|-----------------|
| Type                    | LED             |
| Gross luminous flux     | 955 lm          |
| Colour temperature      | 3500 K          |
| Chromatic stability     | MacAdam Step 2  |
| Colour Rendering Index  | CRI>90          |
| Power                   | 7 W             |
| Current                 | 200 mA          |
| Efficacy                | 136 lm/W        |
| LED lifespan            | L90B10 >55.000h |
| Energy efficiency class | E               |

|                     |     |
|---------------------|-----|
| Lighting efficiency | 73% |
| Light beam angle    | 46° |

|                             |                          |
|-----------------------------|--------------------------|
| Driver                      | Included - Fast Connect  |
| Power values of the system  | 8,25 W                   |
| Frequency                   | 50/60 Hz                 |
| Dimming                     | No Dim                   |
| Electrical insulation class | <input type="checkbox"/> |

|   |                                     |
|---|-------------------------------------|
| Sealing   | IP65                                |
| Impact resistance                               | IK07                                |
| Recess measurements                             | Ø75 mm                              |
| Weight  | 215 g                               |
| Packaged weight                                 | 255 g                               |
| Packaging dimensions                            | 147 x 132 x 134 mm                  |
| Units per package                               | 1                                   |
| Materials                                       | Aluminium / Polycarbonate           |
| Compatible avec la norme française RT2012 & BBC | Oui. Recouvrable d'isolant déroulé. |

## PRODUCT

## LIGHT SOURCE

## LIGHTING FIXTURE | PHOTOMETRIC DATA


## LIGHTING FIXTURE | ELECTRICAL DATA

## OTHER DATA




Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.

## Polar diagram



cd/klm — C0 - C180 — C90 - C270 η = 73%

## Conical diagram



Distance [m] Cone Diameter [m] Illuminance [lx]  
— C0 - C180 (Half-value Angle: 45.6°)

## UGR

### Glare Evaluation According to UGR

| ρ Ceiling  | 70   | 70   | 50   | 50   | 30   | 70                                      | 70   | 50   | 50   | 30   |      |
|--|--|------|------|------|------|---|------|------|------|------|------|
| ρ Walls  | 50   | 30   | 50   | 30   | 30   | 50                                      | 30   | 50   | 30   | 30   |      |
| ρ Floor  | 20   | 20   | 20   | 20   | 20   | 20                                      | 20   | 20   | 20   | 20   |      |
| Room Size X Y  | Viewing direction at right angles to lamp axis |      |      |      |      | Viewing direction parallel to lamp axis |      |      |      |      |      |
| 2H   | 2H   | 15.7 | 16.5 | 15.9 | 16.7 | 16.9                                    | 15.7 | 16.5 | 15.9 | 16.7 | 16.9 |
|  | 3H   | 17.5 | 18.2 | 17.8 | 18.4 | 18.7                                    | 17.5 | 18.2 | 17.8 | 18.4 | 18.7 |
|  | 4H   | 18.3 | 19.0 | 18.6 | 19.2 | 19.5                                    | 18.3 | 19.0 | 18.6 | 19.2 | 19.5 |
|  | 6H   | 19.0 | 19.6 | 19.3 | 19.9 | 20.2                                    | 19.0 | 19.6 | 19.3 | 19.9 | 20.2 |
|  | 8H   | 19.3 | 19.9 | 19.7 | 20.2 | 20.5                                    | 19.3 | 19.9 | 19.7 | 20.2 | 20.5 |
| 4H   | 12H  | 19.7 | 20.2 | 20.0 | 20.5 | 20.9                                    | 19.7 | 20.2 | 20.0 | 20.5 | 20.9 |
|  | 2H   | 16.3 | 16.9 | 16.6 | 17.2 | 17.5                                    | 16.3 | 16.9 | 16.6 | 17.2 | 17.5 |
|  | 3H   | 18.3 | 18.9 | 18.7 | 19.2 | 19.5                                    | 18.3 | 18.9 | 18.7 | 19.2 | 19.5 |
|  | 4H   | 19.3 | 19.8 | 19.7 | 20.1 | 20.5                                    | 19.3 | 19.8 | 19.7 | 20.1 | 20.5 |
|  | 6H   | 20.2 | 20.6 | 20.6 | 21.0 | 21.3                                    | 20.2 | 20.6 | 20.6 | 21.0 | 21.3 |
| 8H   | 8H   | 20.6 | 21.0 | 21.0 | 21.4 | 21.8                                    | 20.6 | 21.0 | 21.0 | 21.4 | 21.8 |
|  | 12H  | 21.0 | 21.3 | 21.4 | 21.7 | 22.2                                    | 21.0 | 21.3 | 21.4 | 21.7 | 22.2 |
|  | 4H   | 19.7 | 20.0 | 20.1 | 20.4 | 20.8                                    | 19.7 | 20.0 | 20.1 | 20.4 | 20.8 |
|  | 6H   | 20.7 | 21.0 | 21.2 | 21.5 | 21.9                                    | 20.7 | 21.0 | 21.2 | 21.5 | 21.9 |
|  | 8H   | 21.3 | 21.5 | 21.8 | 22.0 | 22.5                                    | 21.3 | 21.5 | 21.8 | 22.0 | 22.5 |
| 12H  | 12H  | 21.9 | 22.1 | 22.3 | 22.5 | 23.0                                    | 21.9 | 22.1 | 22.3 | 22.5 | 23.0 |
|  | 4H   | 19.7 | 20.0 | 20.1 | 20.4 | 20.9                                    | 19.7 | 20.0 | 20.1 | 20.4 | 20.9 |
|  | 6H   | 20.9 | 21.1 | 21.3 | 21.6 | 22.0                                    | 20.9 | 21.1 | 21.3 | 21.6 | 22.0 |
| 8H   | 21.5   | 21.7 | 22.0 | 22.2 | 22.7 | 21.5                                    | 21.7 | 22.0 | 22.2 | 22.7 |      |
| Variation of the observer position for the luminaire distances S |  |      |      |      |      |   |      |      |      |      |      |
| S = 1.0H   | +1.1 / -0.3                                    |      |      |      |      | +1.1 / -0.3                             |      |      |      |      |      |
| S = 1.5H   | +2.2 / -0.5                                    |      |      |      |      | +2.2 / -0.5                             |      |      |      |      |      |
| S = 2.0H   | +3.5 / -0.8                                    |      |      |      |      | +3.5 / -0.8                             |      |      |      |      |      |
| Standard table   | BK06   |      |      |      |      | BK06                                    |      |      |      |      |      |
| Correction Summand   | 3.2  |      |      |      |      | 3.2                                     |      |      |      |      |      |
| Corrected Glare Indices referring to 955lm Total Luminous Flux   |  |      |      |      |      |   |      |      |      |      |      |



Fuente de luz (LED) reemplazable por un profesional autorizado  
 Replaceable (LED only) light source by an authorized professional.  
 Source lumineuse (LED) remplaçable par un professionnel agréé  
 Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato  
 Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado  
 Replaceable control gear by an authorized professional  
 Dispositif de commande remplaçable par un professionnel agréé  
 Alimentatore sostituibile da parte di un professionista autorizzato  
 Auswechselbares Betriebsgerät durch autorisierten Fachmann

## Instrucciones para el final de vida y la eliminación de los componentes:

### Instructions on end-of-life and component disposal:

### Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

### Istruzioni per il fine vita e lo smaltimento dei componenti:

### Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato  
 Cut the power supply to the luminaire  
 Couper l'alimentation du luminaire  
 Interrompere l'alimentazione dell'apparecchio  
 Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho  
 Remove light source(s) for disposal  
 Retirer la (les) source(s) lumineuse(s) pour l'élimination  
 Rimuovere la/le sorgente/e di luce per lo smaltimento  
 Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho  
 Remove the battery for decommissioning  
 Retirer la batterie pour sa mise au rebut  
 Rimuovere la batteria per la dismissione  
 Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho  
 Remove control gear for disposal  
 Retirer le dispositif de commande pour l'élimination  
 Rimuovere l'alimentatore per lo smaltimento  
 Betriebsgerät zur Entsorgung ausbauen



Enviar los materiales a un centro de recogida RAEE  
 Send the materials to a WEEE collection centre  
 Envoyer les matériaux dans une déchetterie DEEE  
 Inviare i materiali ad un centro di raccolta RAEE  
 Die Materialien in einem WEEE-Zentrum entsorgen

