



DIMENSIONS



ACCESSORIES



CUSTOM ACCESSORIES
(MANDATORY)



WIRE TRIMLESS ACCESSORY



TRIMLESS TOOL

PRODUCT

Name	FIFTY+ H0 SUSP CUSTOM CORNER DIM PUSH 4000K NT
Reference	A4441532NT
Color	Textured black
RAL	9005
Category	CUSTOM SYSTEMS

LIGHT SOURCE

Type	LED
Gross luminous flux	3440 lm
Colour temperature	4000 K
Chromatic stability	MacAdam Step 2
Colour Rendering Index	CRI>90
Power	23,6 W
Current	1050 mA
Efficacy	142 lm/W
LED lifespan	L80B10 >60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	70% / UGR 47%
Light beam angle	104° / UGR 62°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included - Fast Connect
Power values of the system	26,94 W
Frequency	50/60 Hz
Dimming	Push
Electrical insulation class	⚡


OTHER DATA

Sealing	IP20
Wireless control	Please Consult
Cord length	Max. 2 m
Fast adjustment tensioner	Yes
Diffuser included	No
Weight	2960 g
Packaged weight	3880 g
Packaging dimensions	704 x 629 x 100 mm
Units per package	1
Materials	Aluminium / Polycarbonate



Fifty+ is the longitudinal lighting profile for Custom application. Fifty + adds functional light and visual support to highlight the lines, volumes and transitions defined in the architecture. Having an Opal diffuser which disperses the light and a UGR diffuser that reduces the glare angle. Both are installed as a single part along its entire length so as not to interrupt the light beam.

CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR														
		70	70	50	50	30	70	50	50	30	70	50	50	30
Ceiling														
Walls														
Floor														
Room Size	X	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis							
ZH	YH													
2H	2H	16.7	17.7	17.0	18.0	18.2	16.1	17.2	16.6	17.4	17.6	18.1	18.4	18.7
	3H	18.4	19.2	18.2	19.6	19.8	17.2	18.2	17.5	18.4	18.7	19.2	19.6	19.9
	4H	19.0	19.8	19.3	20.1	20.4	17.6	18.5	17.9	18.7	19.0	19.7	19.8	20.0
	6H	19.4	20.2	19.7	20.5	20.8	17.9	18.7	18.2	19.0	19.3	19.8	19.9	20.1
	8H	19.5	20.2	19.6	20.5	20.9	17.9	18.7	18.3	19.0	19.3	19.8	19.9	20.0
4H	12H	19.5	20.3	19.9	20.6	20.9	18.0	18.7	18.4	19.1	19.4	19.8	19.9	20.1
	16H	17.0	17.9	17.3	18.1	18.4	16.5	17.4	16.8	17.7	17.9	18.3	18.4	18.6
	20H	18.9	19.6	19.2	19.9	20.2	17.8	18.6	18.2	18.9	19.2	19.6	19.7	19.9
	24H	19.6	20.2	20.0	20.6	20.9	18.3	19.0	18.7	19.3	19.6	19.8	19.9	20.0
	30H	20.1	20.7	20.4	21.0	21.4	18.7	19.3	19.0	19.6	19.8	19.9	20.0	20.1
8H	36H	20.3	20.8	20.7	21.2	21.6	18.8	19.4	19.3	19.7	20.1	20.3	20.4	20.5
	48H	20.4	20.8	20.8	21.2	21.6	18.9	19.4	19.4	19.8	19.9	20.0	20.1	20.2
	60H	19.7	20.2	20.1	20.6	21.0	18.6	19.1	19.0	19.5	19.5	19.6	19.7	19.8
	72H	20.3	20.7	20.6	21.2	21.6	19.1	19.6	19.5	19.9	20.0	20.1	20.2	20.3
	84H	20.6	20.9	21.0	21.4	21.8	19.3	19.6	19.7	20.1	20.1	20.3	20.4	20.5
12H	120H	20.7	21.0	21.2	21.5	22.0	19.4	19.7	19.9	20.2	20.3	20.4	20.5	20.6
	144H	19.7	20.2	20.1	20.6	21.0	18.6	19.1	19.0	19.5	19.5	19.6	19.7	19.8
	168H	20.4	20.7	20.8	21.2	21.6	19.1	19.5	19.6	19.9	20.0	20.1	20.2	20.3
	192H	20.6	20.9	21.1	21.4	21.9	19.3	19.6	19.8	20.1	20.1	20.3	20.4	20.5
	216H	20.7	21.0	21.1	21.4	21.9	19.3	19.6	19.8	20.1	20.1	20.3	20.4	20.5
Variation of the observer position for the luminaires distance S														
S = 1.0H		+0.3 / -0.3					+0.3 / -0.5							
S = 1.5H		+0.3 / -0.4					+1.2 / -1.2							
S = 2.0H		+0.9 / -0.9					+2.3 / -1.8							
Standard table		BK05					BK03							
Correction														
Summrand		-0.9										-2.4		

Corrected Glare Evaluation according to 1732001 Table 2 Luminous Efficacy

FIFTY+ Diffuser (x meter)	A447-00-00
FIFTY+ UGR Diffuser (x meter)	A447-00-10
FIFTY+ 2 End Cap Kit	A447-00-20- WT NT
FIFTY+ Straight Joiner	A447-00-30
FIFTY+ Suspension Kit	A444-00-20- WT NT
At least 2 units needed. Extra unit each 100 cm required	
FIFTY+ Suspension Power Line	A444-00-00- WT NT
	A444-00-10- WT NT 



COLOUR | WT ☐ RAL 9016 | NT ☒ RAL 9005 |

MATERIAL |  AL |  PC |

WIRE TRIMLESS ACCESSORY

ARKOSLIGHT®

FIFTY SUSPENSION

FEED



PRODUCT	
Model	Mains Trimless
Reference	A023-00-01- W N
Colour	W ☐ RAL 9016 N ☒ RAL 9005
Category	Accessories



PRODUCT	
Model	Mains Thick Trimless
Reference	A023-00-02- W N
Colour	W ☐ RAL 9016 N ☒ RAL 9005
Category	Accessories



Wire Trimless Accessory is a collection of accessories for fitting tensioners and cables to Arkoslight luminaires suspended directly from the ceiling with any visible ceiling rose or fixings. This achieves a minimalist application with a visually tidy finish.

With Wire Trimless Accessory the items adjacent to the ceiling of the standard product (ceiling roses, fixings, driver boxes, etc.) are concealed by a simple recessed application.


Wire Trimless Accessory reduces the visual impact of the installation leading to extremely minimalist aesthetics. The wires come out of the ceiling material as a part of the structure. This detail creates a much purer, more essential layout, particular when several luminaires are fitted in an arrangement.

FASTENING



PRODUCT	
Model	Steel Cable Trimless
Reference	A023-00-05- W N
Colour	W ☐ RAL 9016 N ☒ RAL 9005
Category	Accessories

As many pieces as needed
according to your product



Wire Trimless Accessory is a collection of accessories for fitting tensioners and cables to Arkoslight luminaires suspended directly from the ceiling with any visible ceiling rose or fixings. This achieves a minimalist application with a visually tidy finish.

With Wire Trimless Accessory the items adjacent to the ceiling of the standard product (ceiling roses, fixings, driver boxes, etc.) are concealed by a simple recessed application.

Wire Trimless Accessory reduces the visual impact of the installation leading to extremely minimalist aesthetics. The wires come out of the ceiling material as a part of the structure. This detail creates a much purer, more essential layout, particular when several luminaires are fitted in an arrangement.



INSTALLATION GUIDE

https://youtu.be/sa_xAgj4ji4



PRODUCT

Model	Trimless Tool D20 X D52 MM
Reference	A478-00-01
Category	Accessories





Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES

INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL

INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT

ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI

ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN



Interrumpir la alimentación del aparato

Cut the power supply to the luminaire

Couper l'alimentation du luminaire

Interrompere l'alimentazione dell'apparecchio

Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho

Remove light source(s) for disposal

Retirer la (les) source(s) lumineuse(s) pour l'élimination

Rimuovere la/le sorgente/e di luce per lo smaltimento

Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho

Remove the battery for decommissioning

Retirer la batterie pour sa mise au rebut

Rimuovere la batteria per la dismissione

Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho

Remove control gear for disposal

Retirer le dispositif de commande pour l'élimination

Rimuovere l'alimentatore per lo smaltimento

Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE

Send the materials to a WEEE collection centre

Envoyer les matériaux dans une déchetterie DEEE

Inviare i materiali ad un centro di raccolta RAEE

Die Materialien in einem WEEE-Zentrum entsorgen

