



## Dimensions



## Accessories



CORD ACCESSORY

|                             |   |
|-----------------------------|---|
| Name                        | PIPE BASE 3M FLOOD DIM PH.CUT 4000K WT                      |
| Reference                   | A4881512WT  |
| Colour                      | Textured white  |
| Base Finishing              | Textured white  |
| RAL                         | 9016  |
| Category                    | SUSPENSION  |
| Type                        | LED   |
| Gross luminous flux         | 690 lm  |
| Colour temperature          | 4000 K  |
| Chromatic stability         | MacAdam Step 2  |
| Colour Rendering Index      | CRI>90  |
| Power                       | 6 W   |
| Current                     | 500 mA  |
| Efficacy                    | 115 lm/W  |
| LED lifespan                | L80B10 >60.000h   |
| Energy efficiency class     | F   |
| Lighting efficiency         | 78%   |
| Light beam angle            | 34°   |
| Driver                      | Included  |
| Power values of the system  | 8,28 W  |
| Frequency                   | 50/60 Hz  |
| Dimming                     | Phase Cut - Other DIM, please consult                       |
| Electrical insulation class | <input type="checkbox"/>                                    |
| Sealing                     | IP20  |
| Wireless control            | Please Consult  |
| Cord length                 | Max. 3 m  |
| Fast adjustment tensioner   | No  |
| Weight                      | 660 g   |
| Packaged weight             | 795 g   |
| Packaging dimensions        | 319 x 148 x 77 mm   |
| Units per package           | 1   |
| Materials                   | Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate |

### PRODUCT

### LIGHT SOURCE

### LIGHTING FIXTURE | PHOTOMETRIC DATA

### LIGHTING FIXTURE | ELECTRICAL DATA

### OTHER DATA



Pipe is created from the harmony of fine lines and geometric shapes. With a more compact body and the incorporation of 'The Invisible Black' effect, which contemplates its composition by playing with units by arrangement and height.


Polar diagram



cd/klm  
— C0 - C180    — C90 - C270

η = 78%

Conical diagram



Distance [m]      Cone Diameter [m]

— C0 - C180 (Half-value Angle: 34.4°)

Illuminance [lx]



| PRODUCT   |  |
|-----------|--|
| Model     | Cord Accessory   |
| Reference | 0223-00-00   W   N   |
| Colour    | W <input type="checkbox"/> RAL 9016   N <input type="checkbox"/> RAL9005 |
| Category  | Accessories  |

## Dimensional drawing





## DRIVER

|            |                           |
|------------|---------------------------|
| 0000-94-44 | DRIVER PHASE CUT 7W 500mA |
|------------|---------------------------|

## PHASE CUT DIMMERS TESTED FOR COMPATIBILITY:

| Brand / Manufacturer | Model number  | Dimming Type  |
|----------------------|---------------|---------------|
| Busch-Jaeger         | 6523 U-102    | Trailing edge |
| Busch-Jaeger         | 6523 UR-103   | Trailing edge |
| Niko                 | 310-0190X     | Trailing edge |
| Jung                 | LB-Management | Trailing edge |
| HZC Electric         | AU-P3         | Trailing edge |
| Philips              | SED-200A      | Trailing edge |
| Merten/Schneider     | SBD315RC      | Trailing edge |
| Etman                | ETM327        | Trailing edge |
| Etman                | ETM329        | Trailing edge |
| Etman (EGANT)        | U321V2        | Trailing edge |
| Casambi              | CBU-TED       | Trailing edge |

THE PARTICULAR CONDITIONS OF EACH INSTALLATION AND THE SPECIFICATIONS AND CONDITIONS OF USE OF EACH REGULATOR, MAY DIFFER FROM THOSE CONSIDERED IN THE COMPATIBILITY TESTING, AND AFFECT ITS PERFORMANCE IN SAID INSTALLATION.



Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

## Instrucciones para el final de vida y la eliminación de los componentes:

### Instructions on end-of-life and component disposal:

### Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

### Istruzioni per il fine vita e lo smaltimento dei componenti:

### Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato  
Cut the power supply to the luminaire  
Couper l'alimentation du luminaire  
Interrompere l'alimentazione dell'apparecchio  
Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho  
Remove light source(s) for disposal  
Retirer la (les) source(s) lumineuse(s) pour l'élimination  
Rimuovere la/le sorgente/e di luce per lo smaltimento  
Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho  
Remove the battery for decommissioning  
Retirer la batterie pour sa mise au rebut  
Rimuovere la batteria per la dismissione  
Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho  
Remove control gear for disposal  
Retirer le dispositif de commande pour l'élimination  
Rimuovere l'alimentatore per lo smaltimento  
Betriebsgerät zur Entsorgung ausbauen



Enviar los materiales a un centro de recogida RAEE  
Send the materials to a WEEE collection centre  
Envoyer les matériaux dans une déchetterie DEEE  
Inviare i materiali ad un centro di raccolta RAEE  
Die Materialien in einem WEEE-Zentrum entsorgen

