



		PRODUCT
Name	FLIP RECESSED FLOOD 3500K NT	
Reference	A4910123NT	
Color	Textured black - Other colours, please consult	
RAL	9005	
Category	CEILING RECESSED	
		LIGHT SOURCE
Type	LED	
Gross luminous flux	680 lm	
Colour temperature	3500 K	
Chromatic stability	MacAdam Step 2	
Colour Rendering Index	CRI > 90	
Power	6 W	
Current	500 mA	
Efficacy	113 lm/W	
LED lifespan	L80B10 > 60.000h	
		LIGHTING FIXTURE PHOTOMETRIC DATA
Lighting efficiency	78%	
Light beam angle	34°	
		LIGHTING FIXTURE ELECTRICAL DATA
Driver	Included	
Power values of the system	7,33 W	
Frequency	50/60 Hz	
Dimming	No Dim	
Electrical insulation class	□	
		OTHER DATA
Sealing	IP20	
Wireless control	Please Consult	
Recess measurements	Ø62 mm	
Swivel angle	90°	
Rotation angle	350°	
Weight	285 g	
Packaged weight	370 g	
Packaging dimensions	205 x 120 x 96 mm	
Units per package	1	
Materials	Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate	



Flip Recessed is integrated into the space in a recessed, functional and flexible version. The luminaire tilts smoothly and its arm is integrated into its vertical geometry for a compact design.

POLAR DIAGRAM



CONICAL DIAGRAM





Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

INSTRUCCIONES PARA EL FINAL DE VIDA Y LA ELIMINACIÓN LOS COMPONENTES
INSTRUCTIONS ON END-OF-LIFE AND COMPONENT DISPOSAL
INSTRUCTIONS POUR LA GESTION DES COMPOSANTS EN FIN DE VIE ET LEUR MISE AU REBUT
ISTRUZIONI PER IL FINE VITA E LO SMALTIMENTO DEI COMPONENTI
ANWEISUNGEN ZUR ENTSORGUNG DER LEUCHTENKOMPONENTEN



Interrumpir la alimentación del aparato
Cut the power supply to the luminaire
Couper l'alimentation du luminaire
Interrompere l'alimentazione dell'apparecchio
Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho
Remove light source(s) for disposal
Retirer la (les) source(s) lumineuse(s) pour l'élimination
Rimuovere la/le sorgente/e di luce per lo smaltimento
Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho
Remove the battery for decommissioning
Retirer la batterie pour sa mise au rebut
Rimuovere la batteria per la dismissione
Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho
Remove control gear for disposal
Retirer le dispositif de commande pour l'élimination
Rimuovere l'alimentatore per lo smaltimento
Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE
Send the materials to a WEEE collection centre
Envoyer les matériaux dans une déchetterie DEEE
Inviare i materiali ad un centro di raccolta RAEE
Die Materialien in einem WEEE-Zentrum entsorgen

