




## Dimensions



## Accessories



DRIVER OPTIONS



CANOPY OPTIONS  
(MANDATORY)

## PRODUCT

|           |                          |
|-----------|--------------------------|
| Name      | DIVI DIRECT END 3000K WT |
| Reference | A5380131WT               |
| Color     | Textured white           |
| RAL       | 9016                     |
| Category  | CUSTOM SYSTEMS           |

## LIGHT SOURCE

|                         |                 |
|-------------------------|-----------------|
| Type                    | LED             |
| Gross luminous flux     | 1650 lm         |
| Colour temperature      | 3000 K          |
| Chromatic stability     | MacAdam Step 2  |
| Colour Rendering Index  | CRI>90          |
| Power                   | 13,5 W          |
| Efficacy                | 122 lm/W        |
| LED lifespan            | L80B10 >60.000h |
| Energy efficiency class | E               |

## LIGHTING FIXTURE | PHOTOMETRIC DATA

|                     |      |
|---------------------|------|
| Lighting efficiency | 58%  |
| Light beam angle    | 115° |

## LIGHTING FIXTURE | ELECTRICAL DATA

|                             |                      |
|-----------------------------|----------------------|
| Driver                      | Excluded             |
| Dimming                     | No Dim / DALI / Push |
| Electrical insulation class | II                   |


## OTHER DATA

|                           |                           |
|---------------------------|---------------------------|
| Sealing                   | IP20                      |
| Cord length               | Max. 2 m                  |
| Fast adjustment tensioner | Yes                       |
| Diffuser included         | Yes                       |
| Weight                    | 1455 g                    |
| Packaged weight           | 1962 g                    |
| Packaging dimensions      | Ø81 x 1235 mm             |
| Units per package         | 1                         |
| Materials                 | Aluminium / Polycarbonate |




The Divi suspension was developed as a contemporary reinterpretation of the most fundamental industrial forms. The design of this product was created by Norwegian designer Lars Tørnøe. Its concept is based on the division and precise longitudinal cut of an aluminum cylinder that pivots on its own axis. By combining successive modules of direct and indirect light, Divi facilitates an infinite number of decorative compositions, both open and closed.

Polar diagram



Conical diagram





| CONSTANT VOLTAGE<br>LED POWER SUPPLY |            | P                                                                                                | V   | Nº of modules |
|--------------------------------------|------------|--------------------------------------------------------------------------------------------------|-----|---------------|
| ON/OFF                               | 0434-01-62 | 150W                                                                                             | 48V | 2 - 8         |
| DIM DALI / PUSH                      | 0434-02-16 | 100W                                                                                             | 48V | 2 - 6         |
| 220<br>240 V~                        |            | To be installed with the DIVI INITIAL or INITIAL & END modules<br>Driver can be placed on remote |     |               |

Connection diagram:



| DROP<br>VOLTAGE<br>TABLE | CABLE LENGTH* (m) |     |     |
|--------------------------|-------------------|-----|-----|
|                          | <10               | <20 | <30 |
| POWER (W)                | MAX Nº OF MODULES |     |     |
| 100                      | 6                 | 6   | 6   |
| 150                      | 8                 | 7   | 6   |


MANDATORY FOR INSTALLATION

Ceiling canopy

Select the most suitable canopy type according to the technical requirements of your installation.


Recessed

Recessed Canopy  
A538-00-00- | WT | NT |



Surface + remote driver


Surface Remote feed kit 48V  
A538-00-11- | WT | NT |



Surface

Surface ON/OFF Box 48V  
A538-00-21- | WT | NT |



Surface DALI Box 48V  
A538-00-22- | WT | NT |



# Divi custom system examples

# ARKOSLIGHT

MINIMUM ASSEMBLY: 2 PROFILES





Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

## Instrucciones para el final de vida y la eliminación de los componentes:

### Instructions on end-of-life and component disposal:

### Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

### Istruzioni per il fine vita e lo smaltimento dei componenti:

### Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato  
Cut the power supply to the luminaire  
Couper l'alimentation du luminaire  
Interrompere l'alimentazione dell'apparecchio  
Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho  
Remove light source(s) for disposal  
Retirer la (les) source(s) lumineuse(s) pour l'élimination  
Rimuovere la/le sorgente/e di luce per lo smaltimento  
Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho  
Remove the battery for decommissioning  
Retirer la batterie pour sa mise au rebut  
Rimuovere la batteria per la dismissione  
Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho  
Remove control gear for disposal  
Retirer le dispositif de commande pour l'élimination  
Rimuovere l'alimentatore per lo smaltimento  
Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE  
Send the materials to a WEEE collection centre  
Envoyer les matériaux dans une déchetterie DEEE  
Inviare i materiali ad un centro di raccolta RAEE  
Die Materialien in einem WEEE-Zentrum entsorgen

