


Dimensions




|                                     |                                     |
|-------------------------------------|-------------------------------------|
| PRODUCT                             |                                     |
| Name                                | REC ASYMMETRIC 4000K PAINT          |
| Reference                           | A5520012PR                          |
| Colour                              | Primer coating                      |
| Category                            | WALL                                |
| LIGHT SOURCE                        |                                     |
| Type                                | LED                                 |
| Gross luminous flux                 | 6080 lm                             |
| Colour temperature                  | 4000 K                              |
| Chromatic stability                 | MacAdam Step 2                      |
| Colour Rendering Index              | CRI>90                              |
| Power                               | 39,8 W                              |
| Current                             | 400 mA                              |
| Efficacy                            | 153 lm/W                            |
| LED lifespan                        | L80B10 >72.000h                     |
| Energy efficiency class             | D                                   |
| LIGHTING FIXTURE   PHOTOMETRIC DATA |                                     |
| Lighting efficiency                 | 51%                                 |
| Light beam angle                    | 79°                                 |
| LIGHTING FIXTURE   ELECTRICAL DATA  |                                     |
| Driver                              | Included                            |
| Power values of the system          | 43,41 W                             |
| Frequency                           | 50/60 Hz                            |
| Dimming                             | No Dim                              |
| Electrical insulation class         | ⏏                                   |
| OTHER DATA                          |                                     |
| Sealing                             | IP20                                |
| Wireless control                    | Please Consult                      |
| Weight                              | 1732 g                              |
| Packaged weight                     | 1847 g                              |
| Packaging dimensions                | 408 x 190 x 48 mm                   |
| Units per package                   | 1                                   |
| Materials                           | Aluminium / Polymethyl Methacrylate |




Rec is a LED appliance that is especially ideal to carry out indirect lighting functions. This is a luminary that perfectly fits into projects that prioritise the comfort given by indirect lighting but also require a high volume of light. Formally, Rec is expressed in a slender cuboid with pure lines and a minimalist design.

Polar diagram



Conical diagram





Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

## Instrucciones para el final de vida y la eliminación de los componentes:

### Instructions on end-of-life and component disposal:

### Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

### Istruzioni per il fine vita e lo smaltimento dei componenti:

### Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato  
Cut the power supply to the luminaire  
Couper l'alimentation du luminaire  
Interrompere l'alimentazione dell'apparecchio  
Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho  
Remove light source(s) for disposal  
Retirer la (les) source(s) lumineuse(s) pour l'élimination  
Rimuovere la/le sorgente/e di luce per lo smaltimento  
Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho  
Remove the battery for decommissioning  
Retirer la batterie pour sa mise au rebut  
Rimuovere la batteria per la dismissione  
Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho  
Remove control gear for disposal  
Retirer le dispositif de commande pour l'élimination  
Rimuovere l'alimentatore per lo smaltimento  
Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE  
Send the materials to a WEEE collection centre  
Envoyer les matériaux dans une déchetterie DEEE  
Inviare i materiali ad un centro di raccolta RAEE  
Die Materialien in einem WEEE-Zentrum entsorgen

