




Dimensions




Name	PUCK OUTDOOR 2700K GT
Reference	A5631000GT
Colour	Textured grey
RAL	7021
Category	OUTDOOR
PRODUCT	
Type	LED
Gross luminous flux	635 lm
Colour temperature	2700 K
Chromatic stability	MacAdam Step 3
Colour Rendering Index	CRI>90
Power	8 W
Efficacy	79 lm/W
LED lifespan	L70B10 >50.000h
Energy efficiency class	G
LIGHT SOURCE	
Lighting efficiency	75%
Light beam angle	38°
LIGHTING FIXTURE PHOTOMETRIC DATA	
LIGHTING FIXTURE ELECTRICAL DATA	
Driver	Included
Frequency	50/60 Hz
Dimming	No Dim
Electrical insulation class	⊕
OTHER DATA	
Sealing	IP65
Outdoor Use	Yes
Weight	470 g
Packaged weight	520 g
Packaging dimensions	111 x 103 x 89 mm
Units per package	1
Materials	Aluminium / Optical Glass



The Puck downlight brings its jewel-like essence to outdoor environments. Maintaining its aluminum body and iconic glass sphere, Puck Outdoor integrates subtly into overhead planes.


Polar diagram



cd/klm
 — C0 - C180 — C90 - C270

η = 75%

Conical diagram



Distance [m] Cone Diameter [m] Illuminance [lx]
 — C0 - C180 (Half-value Angle: 38.4°)
 — C90 - C270 (Half-value Angle: 38.2°)

UGR

Glare Evaluation According to UGR

ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	7.9	8.7	8.2	8.9	9.1	8.0	8.7	8.2	8.9	9.1
	3H	9.2	9.8	9.5	10.1	10.3	9.2	9.9	9.5	10.1	10.3
	4H	10.4	11.0	10.7	11.2	11.5	10.4	11.0	10.7	11.3	11.5
	6H	11.2	11.8	11.5	12.0	12.3	11.2	11.8	11.6	12.1	12.4
	8H	11.5	12.0	11.8	12.3	12.6	11.5	12.1	11.9	12.4	12.7
12H	11.7	12.2	12.1	12.5	12.8	11.8	12.3	12.1	12.6	12.9	
4H	2H	8.2	8.8	8.5	9.1	9.3	8.2	8.8	8.5	9.1	9.4
	3H	9.9	10.5	10.3	10.8	11.1	10.0	10.5	10.3	10.8	11.1
	4H	11.4	11.8	11.8	12.2	12.5	11.4	11.8	11.8	12.2	12.5
	6H	12.4	12.8	12.8	13.1	13.5	12.4	12.8	12.8	13.1	13.5
	8H	12.7	13.1	13.2	13.5	13.9	12.8	13.1	13.2	13.5	13.9
12H	13.0	13.3	13.5	13.7	14.2	13.1	13.4	13.5	13.8	14.2	
8H	4H	11.9	12.2	12.3	12.6	13.0	11.9	12.2	12.3	12.6	13.0
	6H	13.0	13.3	13.5	13.7	14.1	13.0	13.3	13.5	13.7	14.2
	8H	13.5	13.7	13.9	14.1	14.6	13.5	13.7	14.0	14.2	14.6
	12H	13.9	14.1	14.4	14.5	15.0	13.9	14.1	14.4	14.6	15.1
	12H	4H	11.9	12.2	12.3	12.6	13.0	11.9	12.2	12.4	12.6
6H		13.1	13.3	13.6	13.8	14.3	13.1	13.4	13.6	13.8	14.3
8H		13.6	13.8	14.1	14.3	14.8	13.7	13.8	14.2	14.3	14.8
Variation of the observer position for the luminaire distances S											
S = 1.0H	+2.1 / -2.3					+2.2 / -2.3					
S = 1.5H	+4.3 / -2.8					+4.3 / -2.8					
S = 2.0H	+6.1 / -3.3					+6.1 / -3.3					
Standard table	BK02					BK02					
Correction	-1.4					-1.4					
Summand	-1.4					-1.4					
Corrected Glare Indices referring to 635lm Total Luminous Flux											



Fuente de luz (LED) reemplazable por un profesional autorizado
 Replaceable (LED only) light source by an authorized professional.
 Source lumineuse (LED) remplaçable par un professionnel agréé
 Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato
 Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado
 Replaceable control gear by an authorized professional
 Dispositif de commande remplaçable par un professionnel agréé
 Alimentatore sostituibile da parte di un professionista autorizzato
 Auswechselbares Betriebsgerät durch autorisierten Fachmann

Instrucciones para el final de vida y la eliminación de los componentes:

Instructions on end-of-life and component disposal:

Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

Istruzioni per il fine vita e lo smaltimento dei componenti:

Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato
 Cut the power supply to the luminaire
 Couper l'alimentation du luminaire
 Interrompere l'alimentazione dell'apparecchio
 Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho
 Remove light source(s) for disposal
 Retirer la (les) source(s) lumineuse(s) pour l'élimination
 Rimuovere la/le sorgente/e di luce per lo smaltimento
 Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho
 Remove the battery for decommissioning
 Retirer la batterie pour sa mise au rebut
 Rimuovere la batteria per la dismissione
 Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho
 Remove control gear for disposal
 Retirer le dispositif de commande pour l'élimination
 Rimuovere l'alimentatore per lo smaltimento
 Betriebsgerät zur Entsorgung ausbauen



Enviar los materiales a un centro de recogida RAEE
 Send the materials to a WEEE collection centre
 Envoyer les matériaux dans une déchetterie DEEE
 Inviare i materiali ad un centro di raccolta RAEE
 Die Materialien in einem WEEE-Zentrum entsorgen

