




## Dimensions



## Accessories



DRIVER OPTIONS

## Awards



## PRODUCT

|           |                        |
|-----------|------------------------|
| Name      | PUCK M REMOTE 2700K NT |
| Reference | A5771000NT             |
| Colour    | Textured black         |
| RAL       | 9005                   |
| Category  | SURFACE                |

## LIGHT SOURCE

|                         |                 |
|-------------------------|-----------------|
| Type                    | LED             |
| Gross luminous flux     | 1125 lm         |
| Colour temperature      | 2700 K          |
| Chromatic stability     | MacAdam Step 2  |
| Colour Rendering Index  | CRI>90          |
| Power                   | 8,8 W           |
| Efficacy                | 128 lm/W        |
| LED lifespan            | L80B10 >60.000h |
| Energy efficiency class | E               |

## LIGHTING FIXTURE | PHOTOMETRIC DATA

|                     |      |
|---------------------|------|
| Lighting efficiency | 75%  |
| Light beam angle    | 44°  |
| UGR                 | < 19 |

## LIGHTING FIXTURE | ELECTRICAL DATA

|                             |                                    |
|-----------------------------|------------------------------------|
| Driver                      | Excluded: Must be placed on remote |
| Dimming                     | No Dim / DALI / Phase Cut          |
| Electrical insulation class | II                                 |


## OTHER DATA

|                      |                           |
|----------------------|---------------------------|
| Sealing              | IP20                      |
| Weight               | 275 g                     |
| Packaged weight      | 320 g                     |
| Packaging dimensions | 112 x 100 x 60 mm         |
| Units per package    | 1                         |
| Materials            | Aluminium / Optical Glass |



Puck is a luminaire that –for its function, opening angle and luminous flux- manages to embody, in a surface piece, the performance of the classic recessed luminaires with dichroic lamps. Puck is designed to undertake general lighting functions and, moreover, given its ultra-compact format, aims to conserve discretion in those places where it is impossible to recess the appliances in the ceiling.






| PUCK M Remote                                                                                 |            | n Luminaires  | P    | I     | CCT   |         | Flux |
|-----------------------------------------------------------------------------------------------|------------|---------------|------|-------|-------|---------|------|
| DRIVER OPTIONS                                                                                |            |               |      |       |       |         |      |
|  NO DIM    | 0433-00-28 | 1 to 2 Puck M | 8,8W | 500mA | 2700K | 1125 lm |      |
|                                                                                               |            |               |      |       | 3000K | 1200 lm |      |
|  DALI      | 0434-00-44 | 1 to 2 Puck M |      |       | 3500K | 1220 lm |      |
|                                                                                               |            |               |      |       | 4000K | 1270 lm |      |
|  PHASE CUT | 0434-02-47 | 1 Puck M      |      |       |       |         |      |

220  
240

V~

220  
240 V~



## DRIVER

|            |                         |
|------------|-------------------------|
| 0000-86-25 | DRIVER PH.CUT 500mA 10W |
|------------|-------------------------|

## PHASE CUT DIMMERS TESTED FOR COMPATIBILITY:

| Brand / Manufacturer | Model number                | Dimming Type  |
|----------------------|-----------------------------|---------------|
| Busch                | 6523 U-102                  | Universal     |
| Clipsal              | 32E450TM                    | Trailing edge |
| Clipsal              | 32E450UDM                   | Universal     |
| ELKO                 | 316GLE                      | Trailing edge |
| ELKO                 | 315GLE-2Pole                | Trailing edge |
| ELKO                 | 315GLE                      | Trailing edge |
| Feller               | 40200.LED.F.61              | Universal     |
| GIRA                 | 117600/I01                  | Trailing edge |
| Jung                 | 225 TDE                     | Trailing edge |
| Jung                 | 225NVDE                     | Leading edge  |
| Jung                 | 254 UDIE 1                  | Universal     |
| NIKO                 | 325                         | Universal     |
| SAL                  | SDA450                      | Trailing edge |
| SAL                  | SDD350                      | Trailing edge |
| Siemens              | 5TCB 257                    | Leading edge  |
| Clipsal              | 32ELED                      | Trailing edge |
| DIGINET/ MMDM        | 04-B3218-H                  | Trailing edge |
| DIGINET/ MEDM        | 04-B1218-D                  | Trailing edge |
| SG Bluetooth         | 820322                      | Trailing edge |
| GIRA                 | 6523U                       | Leading edge  |
| Sunny                | SDD400U                     | Trailing edge |
| Clipsal              | 31E2PUDM                    | Trailing edge |
| Trader               | DIMR Trader Dimpala Eclipse | Trailing edge |
| SCHNEIDER            | SBD315RC                    | Trailing edge |
| VARILIGHT            | JQP401W                     | Trailing edge |
| MK                   | K1521 WHILV                 | Trailing edge |

THE PARTICULAR CONDITIONS OF EACH INSTALLATION AND THE SPECIFICATIONS AND CONDITIONS OF USE OF EACH REGULATOR, MAY DIFFER FROM THOSE CONSIDERED IN THE COMPATIBILITY TESTING, AND AFFECT ITS PERFORMANCE IN SAID INSTALLATION.

FOR MORE INFO, PLEASE CONSULT



Fuente de luz (LED) reemplazable por un profesional autorizado

Replaceable (LED only) light source by an authorized professional.

Source lumineuse (LED) remplaçable par un professionnel agréé

Sorgente luminosa (LED) sostituibile da parte di un professionista autorizzato

Austauschbare (LED) Lichtquelle durch einen autorisierten Fachmann



Equipo de control reemplazable por un profesional autorizado

Replaceable control gear by an authorized professional

Dispositif de commande remplaçable par un professionnel agréé

Alimentatore sostituibile da parte di un professionista autorizzato

Auswechselbares Betriebsgerät durch autorisierten Fachmann

## Instrucciones para el final de vida y la eliminación de los componentes:

### Instructions on end-of-life and component disposal:

### Instructions pour la gestion des composants en fin de vie et leur mise au rebut :

### Istruzioni per il fine vita e lo smaltimento dei componenti:

### Anweisungen zur entsorgung der Leuchtenkomponenten:



Interrumpir la alimentación del aparato

Cut the power supply to the luminaire

Couper l'alimentation du luminaire

Interrompere l'alimentazione dell'apparecchio

Stromversorgung der Leuchte unterbrechen



Quitar la(s) fuente(s) de luz para el desecho

Remove light source(s) for disposal

Retirer la (les) source(s) lumineuse(s) pour l'élimination

Rimuovere la/le sorgente/e di luce per lo smaltimento

Lichtquelle(n) zur Entsorgung entfernen



Quitar la batería para el desecho

Remove the battery for decommissioning

Retirer la batterie pour sa mise au rebut

Rimuovere la batteria per la dismissione

Die Batterie ordnungsgemäß entsorgen



Quitar el equipo de control para el desecho

Remove control gear for disposal

Retirer le dispositif de commande pour l'élimination

Rimuovere l'alimentatore per lo smaltimento

Betriebsgerät zur Entsorgung ausbauen

Enviar los materiales a un centro de recogida RAEE

Send the materials to a WEEE collection centre

Envoyer les matériaux dans une déchetterie DEEE

Inviare i materiali ad un centro di raccolta RAEE

Die Materialien in einem WEEE-Zentrum entsorgen

