
# Top

ARKOSLIGHT



## Dimensions




## Accessories



BEAM MIXER DIFFUSER



ANTI-GLARE HONEYCOMB LOUVER

## Awards

archiproducts DESIGN AWARDS – WINNER 2018

EUROPEAN PRODUCT DESIGN AWARD

| | |
|---|---|
| | **PRODUCT** |
| **Name** | TOP MINI UL 30º 4000K WT |
| **Reference** | U2960122WT |
| **Color** | Textured white |
| **RAL** | 9016 |
| **Category** | SURFACE |
| | **MOUNTING ACCESSORY / DRIVER** |
| **Mounting Accessory / Driver** | Mandatory, not included. See Mounting acc. Page |
| **Model** | REMOTE BOX 5.6-33W 700mA |
| **Reference** | U100003602 |
| | **LIGHT SOURCE** |
| **Type** | LED |
| **Gross luminous flux** | 655 Lm |
| **Color temperature** | 4000 K |
| **Chromatic stability** | MacAdam Step 2 |
| **Color Rendering Index** | CRI>90 |
| **Power** | 6.5 W |
| **Current** | 700 mA |
| **Efficacy** | 101 Lm/W |
| **LED lifespan** | L90B10>55.000h |
| | **LIGHTING FIXTURE \| PHOTOMETRIC DATA** |
| **Lighting efficiency** | 89% |
| **Delivered luminous flux** | 583 Lm |
| **Light beam angle** | 30° |
| | **LIGHTING FIXTURE \| ELECTRICAL DATA** |
| **Power values of the system** | 8.8 W |
| **Voltage** | 120-277 V |
| **Frequency** | 50/60 Hz |
| **Dimming** | 0-10V |
| | **OTHER DATA** |
| **IC Rated** | Yes |
| **Environmental location** | DAMP |
| **Weight** | 0.128 lb \| 58 gr |
| **Packaged weight** | 0.187 lb \| 85 gr |
| **Packaging dimensions** | 5.35 x 2.68 x 2.01 in \| 136 x 68 x 51 mm |
| **Materials** | Aluminium - Polycarbonate |

Top is a miniaturized surface-mounted ceiling luminaire. Its compact design makes Top an ideal solution for installation in ceiling cavities and for projects where a discrete presence of the luminaire in the scene is desired. Formally Top presents itself as a design of pure lines and architectural aesthetics. In terms of lighting, Top offers a conical distribution with three available beam angles (flood, medium and spot).

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com




5 Year GUARANTEE

# Mounting Accessory / Driver

ARKOSLIGHT

## Mandatory / Not Included




| | PRODUCT |
|---|---|
| Model | REMOTE BOX 5.6-33W 700mA |
| Driver | Included |
| Reference | U100003602 |
| IC Rated | Yes |
| Dimming | 0-10V |
| Size | 7.48 x 3.78 x 1.35 in \| 190 x 94 x 34 mm |
| Weight | 1.8 lb \| 820 gr |
| Packaged weight | 1.93 lb \| 875 gr |
| Packaging dimensions | 9.53 x 4.13 x 1.54 in \| 242 x 105 x 39 mm |
| Nº Luminaires | 1 to 5 |
| LED - Driver Distance | Maximum suggested distance is 16 feet |

| | INPUT CHARACTERISTICS |
|---|---|
| Input Voltage | 120-277 V |
| Frequency | 50/60 Hz |

| | OUTPUT CHARACTERISTICS |
|---|---|
| Output Voltage | 8 - 47 V |
| Output Current | 700 mA |
| Output Power | 5.6 - 33 W |


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com



5Year GUARANTEE

# Wiring Diagram

ARKOSLIGHT




SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com




5Year GUARANTEE

# Lighting Technical Data

ARKOSLIGHT

## Polar diagram





cd/klm

η = 89%

C0 - C180 C90 - C270

## Conical diagram




Distance [m] Cone Diameter [m] Illuminance [lx]

C0 - C180 (Half-value Angle: 31.2°)

## UGR

**Glare Evaluation According to UGR**

| ρ Ceiling | | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| ρ Walls | | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 |
| ρ Floor | | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Room Size X | Y | Viewing direction at right angles to lamp axis | | | | | Viewing direction parallel to lamp axis | | | | |
| 2H | 2H | 6.2 | 6.9 | 6.5 | 7.1 | 7.3 | 6.2 | 6.9 | 6.5 | 7.1 | 7.3 |
| | 3H | 9.8 | 10.4 | 10.0 | 10.6 | 10.8 | 9.8 | 10.4 | 10.0 | 10.6 | 10.8 |
| | 4H | 11.5 | 12.1 | 11.8 | 12.3 | 12.6 | 11.5 | 12.1 | 11.8 | 12.3 | 12.6 |
| | 6H | 13.3 | 13.8 | 13.6 | 14.1 | 14.3 | 13.3 | 13.8 | 13.6 | 14.1 | 14.3 |
| | 8H | 14.2 | 14.7 | 14.5 | 15.0 | 15.3 | 14.2 | 14.7 | 14.5 | 15.0 | 15.3 |
| | 12H | 15.3 | 15.8 | 15.7 | 16.1 | 16.4 | 15.3 | 15.8 | 15.7 | 16.1 | 16.4 |
| 4H | 2H | 7.4 | 8.0 | 7.7 | 8.2 | 8.5 | 7.4 | 8.0 | 7.7 | 8.2 | 8.5 |
| | 3H | 11.1 | 11.5 | 11.4 | 11.8 | 12.2 | 11.1 | 11.5 | 11.4 | 11.8 | 12.2 |
| | 4H | 12.9 | 13.3 | 13.3 | 13.7 | 14.0 | 12.9 | 13.3 | 13.3 | 13.7 | 14.0 |
| | 6H | 14.9 | 15.2 | 15.3 | 15.6 | 16.0 | 14.9 | 15.2 | 15.3 | 15.6 | 16.0 |
| | 8H | 15.9 | 16.2 | 16.3 | 16.6 | 17.0 | 15.9 | 16.2 | 16.3 | 16.6 | 17.0 |
| | 12H | 17.1 | 17.4 | 17.6 | 17.8 | 18.2 | 17.1 | 17.4 | 17.6 | 17.8 | 18.2 |
| 8H | 4H | 13.7 | 14.0 | 14.1 | 14.4 | 14.8 | 13.7 | 14.0 | 14.1 | 14.4 | 14.8 |
| | 6H | 15.9 | 16.1 | 16.3 | 16.5 | 17.0 | 15.9 | 16.1 | 16.3 | 16.5 | 17.0 |
| | 8H | 17.1 | 17.3 | 17.6 | 17.7 | 18.2 | 17.1 | 17.3 | 17.6 | 17.7 | 18.2 |
| | 12H | 18.5 | 18.7 | 19.0 | 19.1 | 19.6 | 18.5 | 18.7 | 19.0 | 19.1 | 19.6 |
| 12H | 4H | 13.9 | 14.1 | 14.3 | 14.5 | 15.0 | 13.9 | 14.1 | 14.3 | 14.5 | 15.0 |
| | 6H | 16.2 | 16.3 | 16.6 | 16.8 | 17.3 | 16.2 | 16.3 | 16.6 | 16.8 | 17.3 |
| | 8H | 17.5 | 17.7 | 18.0 | 18.1 | 18.6 | 17.5 | 17.7 | 18.0 | 18.1 | 18.6 |

Variation of the observer position for the luminaire distances S

| | | |
|---|---|---|
| S = 1.0H<br>S = 1.5H<br>S = 2.0H | +3.4 / -1.8<br>+5.9 / -2.1<br>+7.9 / -2.4 | +3.4 / -1.8<br>+5.9 / -2.1<br>+7.9 / -2.4 |
| Standard table | --- | --- |
| Correction Summand | --- | --- |

Corrected Glare Indices referring to 655lm Total Luminous Flux


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com




5 Year GUARANTEE

# Beam Mixer Diffuser

ARKOSLIGHT



| | PRODUCT |
|---|---|
| Model | Beam Mixer Diffuser |
| Reference | 08050100 |
| Category | Accessories |

NOT SOLD SEPARATELY.

## Beam Mixer Diffuser


The beam mixer diffuser reduces irregularities and distortions caused by parabolic, Fresnel lenses, or TIR collimators, ensuring a more uniform light distribution without significantly increasing beam length.

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia-Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

# Anti-glare Honeycomb Louver

ARKOSLIGHT



| | PRODUCT |
|---|---|
| Model | Anti-glare Honeycomb Louver |
| Reference | 08070000WT |
| Colour | **WT** ☐ \| Textured white |
| Category | Accessories |

NOT SOLD SEPARATELY.

## Anti-glare Honeycomb Louver

Accessory featuring a honeycomb structure designed to control the light beam, reduce glare, and prevent direct exposure to the light source.

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia-Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5Year GUARANTEE