
Black Foster Suspension

ARKOSLIGHT



Dimensions



	PRODUCT
Name	BLACK FOSTER SUSP 1200 UL FLOOD DIM ON BOARD 3500K NTMG
Reference	U3211053NTMG
Color	Textured black-Metallized gold
RAL	Paint of metallic nanoparticles
Category	SUSPENSION

	LIGHT SOURCE
Type	LED
Gross luminous flux	2300 Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	21 W
Current	700 mA
Efficacy	109 Lm/W
LED lifespan	L90B10>102.000h

	LIGHTING FIXTURE | PHOTOMETRIC DATA
Lighting efficiency	92%
Delivered luminous flux	2116 Lm
Light beam angle	38°

	LIGHTING FIXTURE | ELECTRICAL DATA
Driver	Included: ERP-PSB series or similar
Power values of the system	24 W
Frequency	50/60 Hz
Dimming	DIM on Board

	OTHER DATA
Environmental location	DAMP
Junction box cover	Included. For octogonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø5.51 in | Ø140 mm
Cord Length	MAX. 10 ft | MAX. 3.05 m

Awards

Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emisions with dark segments. Nevertheless, wether if it is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

Black Foster Suspension


ARKOSLIGHT



Fast adjustment tensioner	Yes
Weight	7.18 lb | 3255 gr
Packaged weight	9.85 lb | 4470 gr
Packaging dimensions	Ø6.10x50.00 in | Ø155x1270 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate

OTHER DATA

Dimensions



Awards

Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emisions with dark segments. Nevertheless, wether if it is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE


Lighting Technical Data

ARKOSLIGHT

Polar diagram



Conical diagram



UGR

Glare Evaluation According to UGR

ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-8.8	-8.2	-8.6	-8.0	-7.8	-6.1	-5.5	-5.9	-5.3	-5.1
	3H	-7.1	-6.5	-6.8	-6.3	-6.1	-5.7	-5.2	-5.5	-4.9	-4.7
	4H	-6.9	-6.3	-6.6	-6.1	-5.8	-5.7	-5.2	-5.4	-4.9	-4.7
	6H	-5.8	-5.3	-5.5	-5.0	-4.8	-5.3	-4.8	-5.0	-4.5	-4.2
	8H	-5.8	-5.3	-5.5	-5.0	-4.7	-4.8	-4.3	-4.4	-4.0	-3.7
	12H	-5.1	-4.7	-4.8	-4.4	-4.1	-4.2	-3.7	-3.8	-3.4	-3.1
4H	2H	-8.7	-8.2	-8.4	-7.9	-7.6	-6.2	-5.7	-5.9	-5.4	-5.2
	3H	-7.0	-6.6	-6.7	-6.3	-6.0	-5.8	-5.3	-5.4	-5.0	-4.7
	4H	-6.2	-5.8	-5.8	-5.5	-5.1	-5.6	-5.2	-5.3	-4.9	-4.6
	6H	-4.3	-4.0	-3.9	-3.6	-3.3	-4.5	-4.1	-4.1	-3.8	-3.4
	8H	-4.2	-4.0	-3.8	-3.6	-3.2	-3.9	-3.6	-3.5	-3.2	-2.8
	12H	-3.6	-3.3	-3.1	-2.9	-2.5	-3.2	-3.0	-2.8	-2.6	-2.1
8H	4H	-5.9	-5.6	-5.5	-5.2	-4.8	-5.4	-5.1	-5.0	-4.7	-4.3
	6H	-3.7	-3.5	-3.2	-3.1	-2.6	-3.9	-3.7	-3.5	-3.3	-2.8
	8H	-3.5	-3.3	-3.0	-2.9	-2.4	-3.3	-3.2	-2.9	-2.7	-2.3
	12H	-2.8	-2.6	-2.3	-2.2	-1.7	-2.7	-2.5	-2.2	-2.1	-1.6
12H	4H	-5.8	-5.5	-5.3	-5.1	-4.7	-5.3	-5.0	-4.8	-4.6	-4.2
	6H	-3.6	-3.4	-3.2	-3.0	-2.5	-3.8	-3.6	-3.4	-3.2	-2.7
	8H	-3.4	-3.2	-2.9	-2.8	-2.3	-3.3	-3.1	-2.8	-2.7	-2.2

Variation of the observer position for the luminaire distances S

S = 1.0H	+2.4 / -1.3	+3.7 / -1.4
S = 1.5H	+4.3 / -1.5	+6.0 / -1.8
S = 2.0H	+6.3 / -4.1	+8.0 / -2.2
Standard table	BK07	---
Correction Summand	-21.5	---

Corrected Glare Indices referring to 2300lm Total Luminous Flux

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE