
Line 48V

ARKOSLIGHT



Dimensions



Accessories



TRACK 48V OPTIONS

PRODUCT	
Name	LINE 500 48V UL DIM DALI 2700K WT
Reference	U3761020WT
Color	Textured white
RAL	Anodised, bath colour, looks alike RAL 9016
Category	TRACK LIGHTS
LIGHT SOURCE	
Type	LED
Gross luminous flux	1480 Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	10.5 W
Efficacy	141 Lm/W
LED lifespan	L80B10>60.000h
LIGHTING FIXTURE | PHOTOMETRIC DATA	
Lighting efficiency	65%
Delivered luminous flux	962 Lm
Light beam angle	98°
LIGHTING FIXTURE | ELECTRICAL DATA	
Power values of the system	11.5 W
Dimming	DALI
OTHER DATA	
Environmental location	DAMP
Track type	Track 48V
Weight	0.5 lb | 230 gr
Packaged weight	0.88 lb | 400 gr
Packaging dimensions	Ø2.17x21.65 in | Ø55x550 mm
Materials	Aluminium - Polycarbonate

Intertek

Line 48V, is the line-luminary of diffused light for 48 voltage tracklight applications. This lighting solution allows Jokerlight's 48V tracklight to combine accent lighting with longitudinal general lighting where required.


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5Year GUARANTEE


Lighting Technical Data

ARKOSLIGHT

Polar diagram



Conical diagram



UGR

Glare Evaluation According to UGR

ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	23.4	24.7	23.7	24.9	25.2	23.8	25.1	24.1	25.4	25.6
	3H	25.2	26.4	25.5	26.6	26.9	25.5	26.7	25.9	27.0	27.2
	4H	25.9	27.0	26.3	27.3	27.6	26.2	27.3	26.5	27.6	27.8
	6H	26.6	27.6	26.9	27.9	28.2	26.6	27.6	27.0	27.9	28.2
	8H	26.8	27.8	27.2	28.1	28.5	26.7	27.7	27.1	28.0	28.4
	12H	27.1	28.0	27.5	28.4	28.7	26.8	27.8	27.2	28.1	28.4
4H	2H	24.0	25.1	24.4	25.4	25.7	24.4	25.5	24.7	25.8	26.0
	3H	26.0	27.0	26.4	27.3	27.7	26.3	27.3	26.7	27.6	27.9
	4H	26.9	27.8	27.3	28.1	28.5	27.1	27.9	27.5	28.3	28.6
	6H	27.7	28.5	28.1	28.8	29.2	27.7	28.4	28.1	28.8	29.2
	8H	28.1	28.8	28.5	29.1	29.6	27.9	28.5	28.3	28.9	29.3
	12H	28.4	29.0	28.9	29.4	29.9	28.0	28.6	28.4	29.0	29.4
8H	4H	27.3	28.0	27.7	28.4	28.8	27.4	28.1	27.8	28.5	28.9
	6H	28.2	28.8	28.7	29.2	29.7	28.2	28.7	28.6	29.1	29.6
	8H	28.7	29.2	29.2	29.6	30.1	28.5	28.9	28.9	29.4	29.9
	12H	29.2	29.6	29.7	30.1	30.6	28.7	29.1	29.2	29.6	30.1
12H	4H	27.3	27.9	27.8	28.3	28.8	27.5	28.1	27.9	28.5	28.9
	6H	28.3	28.8	28.8	29.3	29.8	28.3	28.8	28.7	29.2	29.7
	8H	28.9	29.3	29.4	29.8	30.3	28.6	29.0	29.1	29.5	30.0

Variation of the observer position for the luminaire distances S

S = 1.0H	+0.1 / -0.1	+0.1 / -0.1
S = 1.5H	+0.2 / -0.3	+0.2 / -0.3
S = 2.0H	+0.3 / -0.7	+0.4 / -0.7
Standard table	BK07	BK06
Correction Summand	9.0	8.5

Corrected Glare Indices referring to 1480lm Total Luminous Flux

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

Track 48V

ARKOSLIGHT

48V track lighting systems are low-voltage lighting solutions based on electrified tracks. The track serves both as a physical structure and as a power carrier, allowing light modules to be placed and repositioned as needed, offering flexibility, safety, and energy efficiency.
Ideal for projects that demand minimalist design, high performance, and adaptability.

To configure your 48V system, you'll need to combine the following components:

1. Tracks – Available in surface, trimless, surface short, suspended (using suspension accessories with the surface track), and indirect light versions. They form the structural and electrical base of the system.


2. Connectors & Power Supply – Ensure electrical continuity between track sections and provide the 48V power input.

3. Accessories – Including end caps, joiners, mounting elements, and optional installation accessories to complete and secure the setup.

Track Options


Surface

TRACK 48V SURFACE 3.28ft (1m) UL	U338-11-00- | NT | WT |
TRACK 48V SURFACE 6.56ft (2m) UL	U338-12-00- | NT | WT |




TRACK 48V SURFACE Corner 90º One Plane UL	U338-14-00- | NT | WT |
TRACK 48V SURFACE T-Joint UL	U338-15-00- | NT |
TRACK 48V SURFACE X-Joint UL	U338-16-00- | NT |


Corner 90º One Plane UL




T-Joint UL



X-Joint UL



Straight joiners included
*Electrical connections not included




Trimless

TRIMLESS INSTALLATION GUIDE
https://youtu.be/tgGsQdaYe-w


TRACK 48V TRIMLESS 3.28ft (1m) UL	U338-01-00- | N | WT |
TRACK 48V TRIMLESS 6.56ft (2m) UL	U338-02-00- | N | WT |
TRACK 48V TRIMLESS Corner 90º One Plane UL	U338-06-00- | N | WT |
TRACK 48V TRIMLESS Corner 90º Two Planes UL	U338-07-00- | N | WT |

Plasterboard ceiling, mandatory thickness 0.50in (12.5mm). Recommended for installations where the profile can be installed before the false plasterboard ceiling.

Track 48V Trimless UL




Corner 90º One Plane UL



*Electrical connection not included

Corner 90º Two Planes UL




*Electrical connection not included


TRACK 48V TRIMLESS DEEPER 4ft (1.21m) UL	U338-31-00- | N | WT |
TRACK 48V TRIMLESS DEEPER 8ft (2.44m) UL	U338-32-00- | N | WT |
TRACK 48V TRIMLESS DEEPER	
Corner 90º One Plane UL	U338-36-00- | N | WT |
Corner 90º Two Planes UL	U338-37-00- | N | WT |

Plasterboard ceiling, mandatory thickness 0.63in (15.9mm). Recommended for installations where the profile can be installed before the false plasterboard ceiling.

Track 48V Trimless Deeper UL




Track 48V Trim. Deeper Corner 90º One Plane UL



*Electrical connection not included

Track 48V Trim. Deeper Corner 90º Two Planes UL



*Electrical connection not included

COLOUR | NT ■ RAL 9005 | WT □ RAL 9016 | N ■ RAL 9005 |

*Electrical connections are not included. Please choose the required components from the Connectors section.

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia-Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

Track 48V


ARKOSLIGHT

Complementary track accessories

Use end caps, joiners, and gap covers to connect, close, and cleanly finish your track setup.


Surface

Surface Straight Joiner 48V UL
U338-00-11



Trimless

Trimless Straight Joiners (2 units) 48V UL
U338-00-05- | N | WT |



For all tracks


End 48V UL
U338-00-06- | NT | WT |



End Feed 48V UL
U338-00-07- | NT | WT |




Cover Gap 3.28ft (1m) 48V UL
U338-00-30- | N | W |




Connector options

Connectors are required to provide electrical continuity between tracks, ensuring an uninterrupted 48V flow.


Live-End Connector 48V UL
U338-00-01- | N | W |




Central Connector 48V UL
U338-00-02- | N | W |




T-Joint Connector 48V UL
U450-00-07- | N |




Wireless Control 48V UL
U434-01-31- | N | W | Casambi




Corner 90º Connector One Plane 48V UL
U338-00-24- | N | W |
*Not suitable for trimless version



L-Joint Connector 48V UL
U338-00-12- | N | W |



X-Joint Connector 48V UL
U450-00-08- | N |



Power Supply Options

Select the appropriate power feed to deliver 48V to the system based on your track layout and installation type.

For all tracks

		P	V	D
CONSTANT VOLTAGE LED POWER SUPPLY	U100-00-78	96W	48V	8.16 x 2.97 x 1.30 in 207 x 75.4 x 33 mm

120 & 277 V | 50/60 Hz

UL DROP VOLTAGE TABLE

		CABLE LENGHT			
		16.40ft 5m	32.80ft 10m	65.62ft 20m	98.43ft 30m
POWER	CABLE SECTION	TRACK LENGHT			
96W	AWG16	164ft 50m	164ft 50m	131.32ft 40m	82ft 25m

COLOUR | N ■ RAL 9005 | W □ RAL 9016 |

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia-Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5Year GUARANTEE


Other accessories

Alternative suspension installation

For a suspended configuration, use surface components together with the following accessories:

Suspension Kit (2 units) 48V UL

U338-00-15- | NT | WT |



Suspension feed Kit 48V UL

U338-00-17- | N | W | DIM

*for remote power supply




Trimless installation accessories

Accessories designed to assist in the installation of trimless track systems, making the process easier and ensuring precision.

Trimless Plaster Installation Guard 3.28ft (1m) 48V UL

U338-00-21


Recommended for installation



Fixing Template for Track 48V Trimless UL

U338-00-31


Recommended for installation



Fixing Template for Track 48V Trimless Deeper UL

U338-30-31

Recommended for installation




Trimless mounting accessories

These accessories offer different options for installing trimless track systems according to ceiling type and project needs.

Trimless T-Bracket 48V UL U338-00-03



Trimless Long T-Bracket 48V UL A338-00-04



Trimless Clamp for M6 ROD 48V UL U338-00-09

*See accessories quantities




Trimless Track Clamp 48V UL U338-00-10

*See accessories quantities



Trimless Suspension Kit 48V UL U338-00-08

*See accessories quantities



SUGGESTED MOUNTING ACCESSORIES QUANTITIES

3.28 ft (1000 mm) - 2 Pcs

6.56 ft (2000 mm) - 3 Pcs

TRIMLESS INSTALLATION GUIDE

https://youtu.be/tgGsQdaYe-w

COLOUR | NT ■ RAL 9005 | WT □ RAL 9016 | N ■ RAL 9005 | W □ RAL 9016 |

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia-Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE