
Buddy

ARKOSLIGHT



Dimensions



	PRODUCT
Name	BUDDY SUPER SPOT UL 4000K NG
Reference	U5070002NG
Color	Black-Gold
RAL	9005 & 1036
Category	CEILING RECESSED

	MOUNTING ACCESSORY / DRIVER
Mounting Accessory / Driver	Mandatory, not included. See Mounting acc. Page
Model	REMOTE BOX 3-10.8W 300mA
Reference	U1000136

	LIGHT SOURCE
Type	LED
Gross luminous flux	530 Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	3.4 W
Current	300 mA
LED lifespan	L80B10>55.000h

	LIGHTING FIXTURE | PHOTOMETRIC DATA
Lighting efficiency	60%
Delivered luminous flux	318 Lm
Light beam angle	12°

	LIGHTING FIXTURE | ELECTRICAL DATA
Power values of the system	5 W
Voltage	120-277 V
Frequency	50/60 Hz
Dimming	0-10V

	OTHER DATA
IC Rated	Yes
Environmental location	DAMP
Recess measurements	Ø3.11 in | Ø79 mm
Weight	0.386 lb | 175 gr
Packaged weight	0.542 lb | 246 gr
Packaging dimensions	5.47 x 4.13 x 3.54 in | 139 x 105 x 90 mm
Materials	Aluminium / Polycarbonate / Polymethyl Methacrylate

The sophistication of recessed lighting. Buddy is designed to maximise the luminous performance of the classic recessed luminaire. It emerges with a solid and purposeful design, greater energy savings and excellent visual comfort. The product family comes in several versions with four opening angles -flood, medium, spot and super spot-. The dim to warm technology enables Buddy to facilitate comfort to the space by dimming the intensity and colour temperature. Furthermore, with the tunable White feature it can be controlled independently. Its four versions per position demonstrate its versatility: recessed, trimless, tilt and the tilt trimless version, which maintains its light output at all opening angles.


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

Mounting Accessory / Driver

ARKOSLIGHT

Mandatory / Not Included



	PRODUCT
Model	REMOTE BOX 3–10.8W 300mA
Driver	Included
Reference	U1000136
IC Rated	Yes
Dimming	0-10V
Size	7.48 x 2.52 x 1.38 in | 190 x 64 x 35 mm
Weight	1.21 lb | 550 gr
Packaged weight	1.93 lb | 875 gr
Packaging dimensions	11.26 x 2.91 x 1.77 in | 286 x 74 x 45 mm
Nº Luminaires	1 to 4
LED - Driver Distance	Maximum suggested distance is 24 feet

	INPUT CHARACTERISTICS
Input Voltage	120-277 V
Frequency	50/60 Hz


	OUTPUT CHARACTERISTICS
Output Voltage	10 - 40 V
Output Current	300 mA
Output Power	3 - 10.8 W

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE

Wiring Diagram

ARKOSLIGHT



SERIAL CONNECTION FOR SEVERAL FIXTURES TO A SINGLE CONSTANT CURRENT DRIVER
RESPECT THE DISTANCE LED - DRIVER


Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5Year GUARANTEE

Lighting Technical Data

ARKOSLIGHT

Polar diagram




cd/klm

η = 60%

C0 - C180 C90 - C270

Conical diagram



Distance [m] Cone Diameter [m] Illuminance [lx]

C0 - C180 (Half-value Angle: 12.6°)

UGR

Glare Evaluation According to UGR

ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-30.4	-29.8	-30.2	-29.6	-29.4	-32.2	-31.6	-32.0	-31.4	-31.2
	3H	-30.5	-30.0	-30.3	-29.7	-29.5	-32.3	-31.8	-32.1	-31.5	-31.3
	4H	-30.6	-30.1	-30.3	-29.8	-29.6	-32.4	-31.9	-32.1	-31.6	-31.4
	6H	-30.7	-30.2	-30.4	-29.9	-29.6	-32.5	-32.0	-32.2	-31.7	-31.4
	8H	-30.7	-30.2	-30.4	-30.0	-29.7	-32.5	-32.0	-32.2	-31.7	-31.5
	12H	-30.8	-30.3	-30.4	-30.0	-29.7	-32.6	-32.1	-32.2	-31.8	-31.5
4H	2H	-30.6	-30.1	-30.3	-29.8	-29.6	-32.4	-31.9	-32.1	-31.6	-31.4
	3H	-30.8	-30.3	-30.4	-30.0	-29.7	-32.6	-32.1	-32.2	-31.8	-31.5
	4H	-30.8	-30.4	-30.5	-30.1	-29.8	-32.6	-32.2	-32.3	-31.9	-31.6
	6H	-30.9	-30.6	-30.5	-30.2	-29.8	-32.7	-32.4	-32.3	-32.0	-31.6
	8H	-30.9	-30.7	-30.5	-30.3	-29.9	-32.7	-32.5	-32.3	-32.1	-31.7
	12H	-31.0	-30.7	-30.6	-30.3	-29.9	-32.8	-32.5	-32.3	-32.1	-31.7
8H	4H	-30.9	-30.7	-30.5	-30.3	-29.9	-32.7	-32.5	-32.3	-32.1	-31.7
	6H	-31.0	-30.8	-30.6	-30.4	-30.0	-32.8	-32.6	-32.4	-32.2	-31.8
	8H	-31.1	-30.9	-30.6	-30.5	-30.0	-32.9	-32.7	-32.4	-32.3	-31.8
	12H	-31.1	-31.0	-30.7	-30.5	-30.0	-32.9	-32.8	-32.4	-32.3	-31.8
12H	4H	-31.0	-30.7	-30.6	-30.3	-29.9	-32.8	-32.5	-32.3	-32.1	-31.7
	6H	-31.1	-30.9	-30.6	-30.5	-30.0	-32.9	-32.7	-32.4	-32.3	-31.8
	8H	-31.1	-31.0	-30.7	-30.5	-30.0	-32.9	-32.8	-32.4	-32.3	-31.8

Variation of the observer position for the luminaire distances S

S = 1.0H	+4.6 / -17.5	+4.5 / -16.9
S = 1.5H	+7.3 / -86.5	+7.3 / -86.4
S = 2.0H	+9.3 / -84.5	+9.3 / -84.4
Standard table	BK00	BK00
Correction Summand	-14.7	-14.8

Corrected Glare Indices referring to 530lm Total Luminous Flux

Calle N, s/n - Pol. Ind. El Oliveral
46394 Ribarroja del Turia - Valencia (Spain)
info@arkoslight.com - www.arkoslight.com

5 Year GUARANTEE